

Loadrite Force

Wheel Loader Scales



- Load more trucks per shift
- Sell more product
- Avoid overload fines

Dynamic, accurate weighing with tip-off and split loading.


Now every machine operator can quickly and easily load trucks exactly to their target weight. The Loadrite™ Force™ helps gauge accurate loading through its no-frills interface. Industry leading weighing accuracy ensures trucks are correctly loaded before they get to the weighbridge (truck scale). This cuts down on congestion and reduces waiting time increasing your customer's satisfaction.

Built on reliable field proven hardware, the Force is a user-friendly, high performance weighing system.

Features

- Accurate and consistent weighing to $\pm 1\%$ of payload reduces haulage costs by eliminating both overloading fines and unnecessary trips caused by under loading.
- Simple to use interface makes weighing fast and easy for all machine operators.

Optional Accessories & Integrations




InsightHQ

Connecting your scale to InsightHQ brings all your quarry productivity information into one easy-to-use dashboard, enabling your team to see progress against targets. You can collect productivity data from your belts, loaders, excavators, haul trucks and more into one location and access it from your desktop or smart device anywhere, anytime.

LP950/LP930 In-cab Printer

Get a hard copy record/customer receipt printed directly from the loader.



Specifications

Weighing Functions

- Dynamic Weighing, Tip-Off Weighing, Split Weighing (e.g. truck and trailer), Target Weighing mode, Over Target Warning, Bucket Overload Warning, Zero, Undo, Auto-Add, Remote-Add, up to 4 different attachments (bucket, forks etc).

Data/Metrics Functions

- Product Short Total, Long Total (Shift) and Bucket Count

Power Requirements

Supply voltage 12 to 32 V DC
 Current consumption 160 mA typical, 350 mA max.
 3 A max. with LP950 printer
 Power supply protection Automotive power supply transient suppression exceeds SAE specifications for DC automotive power supply transients

Physical Specifications

Indicator weight 1.5 kg (3.3 lbs)
 Indicator dimensions W145 x L240 x D110 mm (5.7 x 9.4 x 4.3 in)
 Indicator operating temperature -10°C to 50°C (14°F to 122°F)
 Environmental protection IP69K protected trigger and pressure transducers IP54 protection for indicator

Other Information

- Supported languages:** Danish, Dutch, English, French, German, Hungarian, Italian, Norwegian, Portuguese (Br), Spanish, Swedish
- Supported printing languages:** Dutch, English, French, German, Hungarian, Italian, Portuguese (Br), Spanish, Swedish
- Warranty:** 1 year parts and labor

Contact your local dealer today

BRISBANE	TOWNSVILLE	SYDNEY	SYDNEY - WASTE
U4, 29 Links Avenue North Eagle Farm QLD 4009 P: 1800 655 890 M: 0499 890 093 Reception.QLD@SmartTech.com.au	11-13 Casey Street Townsville QLD 4834 P: 1800 655 890 M: 0499 890 093 Reception.QLD@SmartTech.com.au	U13, 7-9 Progress Circuit Prestons NSW 2170 P: 1800 655 890 M: 0408 964 134 Reception.NSW@SmartTech.com.au	Unit 53 A/13 Endeavour Rd Caringbah NSW 2229 P: 1800 655 890 M: 0419 244 995 Waste@SmartTech.com.au
MELBOURNE	ALBURY/WODONGA	TASMANIA	PERTH
11B The Crossway Campbellfield VIC 3061 P: 1800 655 890 M: 0427 766 125 Reception.VIC@SmartTech.com.au	408/4 Wagga Road Levinton NSW 2641 P: 1800 655 890 M: 0459 965 187 Reception.NSW@SmartTech.com.au	PO Box 315 Newstead TAS 7250 P: 1800 655 890 M: 0427 766 125 Reception.TAS@SmartTech.com.au	U1, 8 Healer Road Osborne Park WA 6017 P: 1800 655 890 M: 0407 912 821 Reception@STechWA.com.au

